

GLASSWASHER S28

Dimensions 47x51,5x68,5 cm.

Basket 40x40 cm.

Wash height 28 cm.

Wash cycle 2 min.

Double tank filter.

Rinse aid dosing.

Micro switch safety door.

Constructed of catering grade 18/8 AISI 304 stainless steel wash tank with integral moulded basket slides.

Double skinned door and outer panels for additional strength and reduced noise levels.

Powerful anti-clog wash arms and contra-rotating light weight rinse arms for optimum results.

Supplied with a COLD RINSE option to chill glasses down after rinsing and TOP stainless steel WASH ARM.



Power supply	V	230V/1
Frequency	Hz	50
Max. power consumed	kW	3,27
Boiler element power	kW	3
Tank element power	kW	1,6
Wash pump power	kW	0,27
Water supply pressure	kPa	200-400
Inlet water supply temperature	°C	55
Water supply hardness	°dF	7 – 12
Water consumption per rinse	l	2,4
Wash water temperature	°C	50 - 60
Rinse water temperature	°C	82 - 85
Boiler capacity	l	2,7
Tank capacity	l	14
Standard cycle duration	s	120
Noise level	dB(A)	48
Protection rating	IPX	1
Net Weight	kg	45
Power cable type	◀HAR▶	H07RN-F