

*High quality AISI 304 Stainless steel construction.*

*Pressed moulded wash tanks with a comprehensive filter system, for quick and easy cleaning.*

*Double skinned outer panel construction to reduce noise levels and surface temperatures.*

*Powerful anti-clog wash arms and contra-rotating light weight rinse arms.*

*All internal components are easily removable for cleaning.*

*1,42 kW wash pump motor self-draining at the end of service.*

*Rinse booster pump.*

*Digital control panel shows the wash and rinse temperatures. Choice of 4 washing cycles.*

*EQUIPMENT: Euronorm trays basket 62x57 cm keeps 11 Euronorm trays 60x40 and Universal basket 62x57 cm.*



# TECHNICAL CHARACTERISTICS

MODEL		LP57
Power supply	V	400V/3+N
Frequency	Hz	50
Max. power consumed	kW	11,42
Boiler element power	kW	10
Tank element power	kW	3
Wash pump power	kW	1,42
Water supply pressure	kPa	200-400
Inlet water supply temperature	°C	55
Water supply hardness	°dF	7 – 12
Water consumption per rinse	l	3
Wash water temperature	°C	50 - 60
Rinse water temperature	°C	82 - 85
Boiler capacity	l	12
Tank capacity	l	35
Standard cycle duration	s	60/120/180/ongoing
Noise level	dB(A)	66
Protection rating	IPX	1
Net Weight	kg	125
Power cable type	◀HAR▶	H07RN-F

Information of this catalogue may contain technical inaccuracies or typographical errors. Information may be changed or updated without notice. Silanos may make improvements and/or changes in the materials contained in or described on this catalogue at any time without notice.

