



## STANDARD FEATURES



Control panel	<b>ELECTRONIC DIGIT2</b>
Wash arm	<b>1 - Stainless steel</b>
Rinse arm	<b>2 - PP</b>
Detergent injector	<b>Optional</b>
Rinse aid injector	<b>Standard</b>
Peristaltic rinse aid injector	<b>Optional</b>
Break tank	<b>Optional</b>
Water softener	<b>Optional</b>
Drain pump	<b>Optional</b>
Diagnose Wi-Fi	<b>-</b>

## TECHNICAL FEATURES

External size	<b>453x511x689</b>	<b>LxPxH</b>	[mm]
Overall size	<b>855</b>	<b>DOA</b>	[mm]
Clearance	<b>300</b>	<b>A</b>	[mm]
Rack size	<b>400x400</b>		[mm]
Tank size	<b>14</b>		[lt]
Rinse water consumption	<b>2,4</b>		[lt]
Wash pump	<b>0,17</b>		[kW]
Tank heater element	<b>1,6</b>		[kW]
Booster heater element	<b>2,8</b>		[kW]
Installed load	<b>2,97</b>		[kW]
Cycles	<b>60 / 120 / 180 / 480</b>		[sec]
Output cycles per hour	<b>60 / 30 / 20 / 8</b>		[cycle/h]
Electrical supply	<b>230V/50Hz</b>		
Noise	<b>48</b>		[dBA]
Weight	<b>33</b>		[kg]

Theoretical data with water supply at 55°C

Where water hardness exceeds 8,43°e, a water softener is required. Not suitable for hot water over 30°C

All data, photos or indications on this technical sheet are given for information and have no contractual value. They are subject to change without notice.

## STANDARD EQUIPMENT

Hoses (1 for each): Water connection, drain, transparent rinsing product  
2 universal baskets, 1 cutlery rack

## GENERAL FEATURES

- Double-skinned cabinet and door.
- Tank and door made of stainless steel AISI 304.
- Easy-clean-dual-filter system.
- Pressed basket guides in the tank.
- Monobloc wash pump fixed directly to the tank.
- A stainless-steel wash arm and two rinse arms of composite material, independent and rotary.
- Integral rinse aid dosing unit.
- Digital control panel (DIGIT2).
- Four purpose-designed washing cycles for various types of crockery to be washed.

## PERFORMANCES

	55°C nom.	15	20	25	30	35	40	45	50	55	60	[°C]
Supply water temperature												
Maximum cycles feasible in continuous operation	<b>48</b>	23	25	27	29	32	36	41	48	48	48	[rack/h]
Total spending power from single-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Total spending power from double-skin machine	<b>3,01</b>	2,95	2,95	2,95	2,94	2,94	3,03	3,02	3,01	3,01	3,01	[kW]
Sensible heat emitted into the local from single-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Sensible heat emitted into the local from double-skin machine	<b>0,33</b>	0,36	0,36	0,36	0,35	0,35	0,34	0,34	0,33	0,33	0,33	[kW]
Latent heat emitted into the local	<b>0,61</b>	0,14	0,17	0,20	0,24	0,29	0,36	0,44	0,56	0,61	0,67	[kW]
Emitted standby power with closed door in single-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Emitted standby power with closed door in double-skin machine	<b>0,12</b>	0,12	0,12	0,12	0,12	0,12	0,12	0,12	0,12	0,12	0,12	[kW]