



## STANDARD FEATURES



Control panel	<b>ELECTRONIC DIGIT3</b>
Wash arm	<b>2 - Stainless steel</b>
Rinse arm	<b>2 - Stainless steel</b>
Detergent injector	<b>Standard</b>
Rinse aid injector	-
Peristaltic rinse aid injector	<b>Standard</b>
Break tank	<b>Optional</b>
Water softener	<b>Optional</b>
Drain pump	<b>Optional</b>
Diagnose Wi-Fi	-

## TECHNICAL FEATURES

External size	<b>655x785x1500</b>	<b>LxPxH</b>	[mm]
Overall size	<b>1.950</b>	<b>DOA</b>	[mm]
Clearance	<b>430</b>	<b>A</b>	[mm]
Maximum height for crockery	<b>405</b>	<b>Au</b>	[mm]
Rack size	<b>500x500</b>		[mm]
Tank size	<b>20</b>		[lt]
Rinse water consumption	<b>2,6</b>		[lt]
Wash pump	<b>0,52</b>		[kW]
Tank heater element	<b>3,0</b>		[kW]
Booster heater element	<b>6,0</b>		[kW]
Installed load	<b>6,5</b>		[kW]
Cycles	<b>120 / 180</b>		[sec]
Output cycles per hour	<b>30 / 20</b>		[cycle/h]
Electrical supply	<b>400V/3N/50Hz</b>		
Noise	<b>63</b>		[dBA]
Weight	<b>117</b>		[kg]

Theoretical data with water supply at 55°C

Where water hardness exceeds 8,43°e, a water softener is required. Not suitable for hot water over 30°C



## STANDARD EQUIPMENT

Hoses (1 for each) Water connection, drain, transparent for rinse product  
Baskets 2x18 plates, 1 universal basket, 2 cutlery rack

## GENERAL FEATURES

- **Single-skinned cabinet.**
- **Press-moulded wash tank with radial corners, inclined to filters**
- **Easy-clean-dual-filter system.**
- **Two stainless-steel wash and two stainless-steel rinse arms, independent and rotary.**
- **Peristaltic rinse aid auto-dosing unit, adjustable from control panel.**
- **Stand-by system for energy saving.**
- **Auto-start hood.**
- **HY-NRG rinse function with break tank, pressure booster pump and insulated atmospheric boiler keeps the set temperature and quantity of water used in for rinse at constant levels.**
- **Digital control panel (DIGIT3).**
- **Four purpose-designed washing cycles for various types of crockery to be washed.**

## PERFORMANCES

	55°C nom.	15	20	25	30	35	40	45	50	55	60	[°C]
Supply water temperature												
Maximum cycles feasible in continuous operation	<b>28</b>	28	28	28	28	28	28	28	28	28	28	[rack/h]
Total spending power from single-skin machine	<b>5,31</b>	6,44	6,44	6,53	6,70	6,00	5,83	5,65	5,48	5,31	5,14	[kW]
Total spending power from double-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Sensible heat emitted into the room from single-skinned machine	<b>1,64</b>	1,64	1,64	1,64	1,64	1,64	1,64	1,64	1,64	1,64	1,64	[kW]
Sensible heat emitted into the room from double-skinned machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Latent heat emitted into the room	<b>1,60</b>	1,13	1,18	1,24	1,29	1,35	1,41	1,47	1,54	1,60	1,67	[kW]
Emitted standby power with closed door in single-skin machine	<b>0,83</b>	0,83	0,83	0,83	0,83	0,83	0,83	0,83	0,83	0,83	0,83	[kW]
Emitted standby power with closed door in double-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]